














































AWUKO Qualities

Name	Characteristics	Grain No.					Areas of Applications		
AWUKO-KP12F antistatic	F-paper, very open coated, aluminium oxide, resin bond	P150-P60	✓	✓	✓			✓	✓
AWUKO-KP52F antistatic	F-paper, semi open coated, aluminium oxide, resin bond	P220-P60, P40	✓	✓	✓			✓	✓
AWUKO-KP80E	E-paper, dense coated, aluminium oxide, resin bond	P800-P36, P24	✓	✓	✓	✓	   	✓	✓
AWUKO-KP80E velcro	our AWUKO KP80E with velcro backing	P150-P36, P24		✓		✓	 	✓	✓
AWUKO-KP80E PSA	our AWUKO KP80E in PSA execution	P600-P400, P320-P40		✓		✓	  	✓	✓
AWUKO-KP81E	E-paper, special coating, aluminium oxide	P400, P320-P180			✓				✓
AWUKO-KP32C	flexible C-Latex paper, semi open coated, aluminium oxide, resin bond	P180-P80		✓	✓	✓	 	✓	✓
AWUKO-KP32C velcro	our AWUKO KP32C with velcro backing	P180-P100		✓	✓	✓	 	✓	✓
AWUKO-KP43E	E-paper, dense coated, aluminium oxide, hide glue	P1500-P100	✓		✓		 		✓
AWUKO-KP20F	F-paper, special coating, aluminium oxide, resin bond	P400, P320-P180	✓		✓				✓
AWUKO-ZP88F inox express	F-paper, dense coated, zircon corundum, resin bond	220-100	✓						✓
AWUKO-KP88F inox express	F-paper, dense coated, aluminium oxide, resin bond	P400, P320-P240	✓						✓
AWUKO-KP63D painter express	D-paper, special wave-form coating, hide glue	P180, P120-P60		✓	✓		 	✓	✓
AWUKO-KP73A	A-paper, semi open coated, aluminium oxide, hide glue	P1000, P800, P600, P400, P320-P60		✓	✓		 	✓	✓
AWUKO-KP73C	C-paper, semi open coated, aluminium oxide, hide glue	P400, P320, P240-P180, P120	✓	✓	✓		 	✓	✓
AWUKO-SP14A	A-paper, special stearate coating, silicon carbide, hide glue	P400, P320-P180		✓	✓	✓	 	✓	✓
AWUKO-SP14A velcro	our AWUKO SP14A with velcro backing	P400, P320-P220		✓	✓	✓	 	✓	✓
AWUKO-SP23B	B-paper, dense coated, silicon carbide, hide glue	P600-P180	✓	✓	✓			✓	✓
AWUKO-SP23E	E-paper, dense coated, silicon carbide, hide glue	P800-P150	✓	✓	✓			✓	✓
AWUKO-SP40E antistatic	E-paper, dense coated, silicon carbide, resin bond	P600-P240	✓	✓	✓	✓	  	✓	✓
AWUKO-SP40F antistatic	F-paper, dense coated, silicon carbide, resin bond	P320-P36, P24	✓	✓	✓	✓	  	✓	✓
AWUKO-SP48G panel express	G-paper, dense coated, silicon carbide, resin bond	P220-P60	✓					✓	✓
AWUKO-SR40A	waterproofed A-paper, silicon carbide, resin bond	P1200-P220		✓				✓	



AWUKO ABRASIVES

Wandmacher GmbH & Co. KG

Name	Characteristics	Grain No.					Areas of Applications		
AWUKO-SR40C	waterproofed C-paper, silicon carbide, resin bond	P180-P60		✓				✓	
AWUKO-KT62XF	x flex cotton cloth, close coated, aluminium oxide, resin bond	P400, P320, P240-P60, P40	✓	✓	✓		  	✓	✓
AWUKO-KT62X	heavy cotton cloth, dense coated, aluminium oxide, resin bond	P180-P36, P24, P16	✓	✓	✓	✓	   	✓	✓
AWUKO-KT82X	X-flex cotton cloth, dense coated, aluminium oxide, resin bond	P120-P36, P24, P16	✓		✓		 	✓	✓
AWUKO-KT62J	medium-soft cotton cloth, dense coated, aluminium oxide, resin bond	P400, P320, P240-P60	✓	✓	✓			✓	✓
AWUKO-KT62F	high-flexible cotton cloth, dense coated, aluminium oxide, resin bond	P800-P60	✓	✓	✓		  	✓	✓
AWUKO-KT20F	soft cotton cloth, dense coated, aluminium oxide, resin bond	P400, P320, P240, P180-P60, P40		✓	✓		 	✓	
AWUKO-ZT62X	heavy cotton cloth, dense coated, zircon corundum, resin bond	120-36, 24	✓		✓	✓	  		✓
AWUKO-ZT62X velcro	heavy cotton cloth, dense coated, zircon corundum, resin bond, velcro backing	120-36, 24				✓			✓
AWUKO-ZU62SY	heavy polyester cloth, dense coated, zircon corundum, resin bond, also for segmented belts	100-36, 24	✓		✓		 		✓
AWUKO-KU22SY panel express	extremely heavy polyester cloth, dense coated, aluminium oxide, resin bond, also for segmented belts	P150-P40	✓		✓	✓	 		✓
AWUKO-KW22X	heavy waterproofed cotton cloth, dense coated, aluminium oxide, resin bond	P600, P400, P320, P240-P180	✓		✓	✓	 		✓
AWUKO-SU22SY panel express	extremely heavy polyester cloth, dense coated, silicon carbide, resin bond, also for segmented belts	P180-P36, P24	✓						✓
AWUKO-SU42Y	heavy polyester cloth, dense coated, silicon carbide, resin bond	P150-P36, P24	✓		✓	✓	  		✓
AWUKO-SW22X	heavy waterproofed cotton cloth, dense coated, silicon carbide, resin bond	P600, P400, P320, P240-P180	✓		✓	✓	  		✓
AWUKO-ST10X	heavy cotton cloth, open coated, silicon carbide, resin bond	P16, P12			✓	✓	  		✓
AWUKO-KN22T	vulcanized fibre, dense coated, aluminium oxide, resin bond	P320-P16				✓			✓
AWUKO-ZN22T	vulcanized fibre, dense coated, zircon corundum, resin bond	P120-P16				✓			✓
AWUKO-KT80X	dense coated, aluminium oxide, resin bond, special quality for naumkeag cap	P220-P60							✓

AWUKO ABRASIVES

Wandmacher GmbH & Co. KG

Hedemündener Straße 9
D-34346 Hann. Münden

E-Mail: info@awuko.de
Website: <http://www.awuko.com>

Telephon: +49 (0)5541 7097-0
Fax national: 05541 6727
Fax international: +49 (0) 5541 6729

AWUKO ABRASIVES
Wandmacher GmbH & Co. KG

Name	Characteristics	Grain No.					Areas of Applications		
AWUKO-OK96L	polishing combination, cotton fabric on sodium kraft paper	-	✓		✓				✓
AWUKO-KP85F	F-Paper, close coated, aluminium oxide, resin bond	P80,P60	✓						✓
Sponges hard	foam sponge, 4-side-coated, aluminium oxide	220-36					 	✓	
Sponges flexible	soft foam sponge, coated on 4 sides, aluminium oxide	180-60					 	✓	
Mats black	soft, flexible foam material, coated on 2 sides, silicon carbide	180-60					 	✓	
Mats white	high flexible foam mat, coated on 1-side	180-60					 	✓	
AWUKO-Fleece A	nylon fibre fleece, aluminium oxide, resin bond	A280-A100	✓	✓	✓		 	✓	✓
AWUKO-Fleece S	nylon fibre fleece, silicon carbide, resin bond	S1000+ S400	✓	✓	✓		 	✓	✓
AWUKO-Sanding Screen	sanding screen, silicon carbide, resin bond	220-60				✓	  		✓
AWUKO-Floor Sanding Pads	available in colour: black, green, maroon, brown, red, beige and white (thin:10mm / thick: 20mm)	-				✓			✓
AWUKO-Graphite Cloth	graphite cloth available in execution 303, GC, 450 and HD	-		✓	✓				✓